

Leica Zeno Tab 2

Rugged Android Tablet



Improve efficiency

The lightweight and easy to use Zeno Tab 2 allows you to work outdoors in demanding conditions. The large bright display and all-day battery allow you to work more efficiently, in all weather conditions.



Stay connected

Easily share data offline or online with WiFi and Sim card. Bluetooth® enables pairing with the Leica GG04 plus smart antenna for centimetre level positioning when used with HxGN SmartNet GNSS correction services.



Keep it simple

The Android operating system ensures easy and flexible operation. When using the Leica Zeno Mobile data collection app, the simple-to-use interface saves time in the field and professional tools help to increase your productivity.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica Zeno Tab 2



TECHNOLOGY

Processor and Memory	Qualcomm MSM8953 Octa-Core 2.2 GHz and 4 GB RAM
Data storage	32 GB on-board extensible with MircoSD
Operating system	Android 8.0
Google Play	Google Mobile Sevices and Google Play Store included
Screen	8" 1280 x 800 VGA capactive sunlight readable touch screen with 400 Nit brightness
Integrated camera	13 megapixel rear and 5 megapixel front camera
Internal GNSS	U-blox M8N GPS/Glonass/Beidou
I/O	USB 2.0 Type C
Additional sensors	Gryroscope, Compass, Accelerometer, Barometer

COMMUNICATION

GSM	GSM, WCDMA, LTE
Bluetooth®	4.1
Wi-Fi	802.11 a/b/g/n/ac
NFC	Included

POWER MANAGEMENT

Battery	Lithium-ion 8200 mAh
Operating time	Up to 15 hours

PHYSICAL SPECIFICATIONS

Size	242 mm x 152 mm x 17.8 mm
Weight	618 g
Water and dust	IP67
Operating temperature range	-20°C to 60°C
Storage temperature range	-40°C to 70°C
Drop	1.2 m drop resistant
MIL-STD	MIL-STD-810G MIL-STD-461F

ACCESSORIES AND OPTIONAL FEATURES

Accessories	Pole holder
Field Software	Leica Zeno Mobile, Leica Zeno Connect
GNSS antenna	Leica GG04 plus

Technology Integrations

HxGN SmartNet

HxGN SmartNet transforms the world's largest reference network into a precise positioning service. Pair the Leica Zeno Tab 2 with the Leica GG04 plus smart antenna and connect to HxGN SmartNet GNSS correction services to enable up-to one centimetre positioning in real-time, allowing for faster and more accurate data collection in the field.

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland – 2019.
Leica Geosystems AG is part of Hexagon AB. 901206en - 07.19

The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Android™ is a trademark of Google Inc.

Leica Geosystems AG
Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31

- when it has to be **right**

Leica
Geosystems